

CF-62-CDH-PP PTFE 62 鐵氟龍藍網化學輸送管

內襯管:



- 螺旋式聚四氟乙烯 PTFE 管/透明白色
- 杜邦 PTFE 62N

外覆網:

- 藍色 PP 軟式網(Braided Blue Polypropylene)



耐溫範圍:

- (-20°F to 250°F)

壓力範圍:

- (250PSI@72°F)

PTFE Convoluted Tubing Sizes

for extra heavy wall see lower table

		Heavy Wall Tubing					Light Wall Tubing				Low Convoluted Tubing				
Size	Wall	ID	OD	Pitch	Min. Bend Radius	Max. Coil Length	Wall	ID	OD	Max. Coil Length	Wall	ID	OD	Pitch	Max. Coil Length
Inch	mm	mm	mm	mm	mm	m	mm	mm	mm	m	mm	mm	mm	mm	m
1/4	0.65	5.9	10	4.5	10	150									
5/16	0.65	8	12.5	5	15	125									
3/8	0.65	10	14.5	5	20	120									
1/2	0.9	13	18	6	25	80					0.75	13	18	6	100
5/8	0.85	16	21.5	6	30	55									
3/4	1.0	20	28	8	50	140	0.90	20	28	160	0.8	20	27	6	160
1	1.1	25	34	8	60	100	0.95	25	34	125	0.95	25	32	7	125
1 1/4	1.15	32	42	10	80	70	0.95	32	43	100	0.95	32	42	7	100
1 1/2	1.45	37	47	10	100	100	0.95	38	49	70	0.95	38	48	8	70
1 3/4	1.45	45	57	12	120	85	0.95	45	56	80					
2	1.5	50	61	12.5	125	80	1.0	50	61	60	1.0	50	60	8	60
2 1/4	1.5	57	73	16	150	65									
2 1/2	1.5	63	82	18	175	55									
3	1.5	74	92	20	200	45									
4	2.0	100	125	24	250	25									
6	2.5	150	185	30	250	15									

Note: Maximum coil length of PTFE conductive tube may be shorter.